Parallel Computational Acoustics Library - Mesh Generation Reference Manual

Frédéric Magoulès, François-Xavier Roux

Parallel Computational Acoustics Library
Mesh Generation Reference Manual*
by F. Magoulès and F.-X. Roux

June 13, 2002

Contents

* Generated by adoC, awk documenting C, June 13, 2002

Index

1 Modules

1.1 mesh_struct

NAME

mesh_struct

SYNOPSIS

```
MODULE mesh_struct
```

DESCRIPTION

Mesh structure for split_mesh program.

ARGUMENTS

nodes_per_element – integer (= number of nodes per element)
numb_elements – integer (= number of elements)
geometry – integer array (= geometry)
space_dim – integer (= number of coordinates per node)
numb_nodes – integer (= number of nodes)
coordinates – real array (coordinates)
numb_clamp_nodes – integer (= number of clamped nodes)
clamp_nodes – integer array (= clamped nodes)
nodes_per_facet – integer (= number of nodes per facet)
numb_facets – integer (= number of facets)
facets – integer array (= facets)
facet2elem – integer array (= facet to element correspondance)
numb_clamp_facets – integer
clamp_facets – integer array (= clamped facets)

2 Functions

2.1 split_mesh

NAME

split_mesh

SYNOPSIS

```
PROGRAM split_mesh
```

DESCRIPTION

Build subdomains from a global domain divided in grid and mesh with regular hexahedrom with all the same material properties: $\omega = 2\pi F/c$, with $c = 1$. The variables ω, F and c denotes respectively the wavenumber, the frequency, and the celerity.

ARGUMENTS

None

MODULES

USE mesh_struct

2.2 split_element

NAME

split_element

SYNOPSIS

```
 SUBROUTINE split_element (ni,nj,nk,nsdi,nsdj,nsdk,                &
&                          subdom_numb,numb_elem,elem2subdom)
```

DESCRIPTION

Decompose regular hexaedric mesh of domain into subdomains and build elements to subdomain correspondance.

ARGUMENTS

ni – integer
nj – integer
nk – integer
nsdi – integer
nsdj – integer
nsdk – integer
subdom_numb – integer
numb_elem – integer
elem2subdom – integer array

2.3 split_facet

NAME

split_facet

SYNOPSIS

```
SUBROUTINE split_facet (dom,elem2dom,facet2dom)
```

DESCRIPTION

Detect facets on rear face of domain.

ARGUMENTS

dom – mesh structure
elem2dom – integer array
facet2dom – integer array

MODULES

USE mesh_struct

2.4 build_glob_dirichlet

NAME

build_glob_dirichlet

SYNOPSIS

```
SUBROUTINE build_glob_dirichlet (front,back,right,left,top,botton, &
&                                dom)
```

DESCRIPTION

Detect clamped nodes on face of domain with the convention front ($x > 0$), back ($x < 0$), right ($y > 0$), left ($y < 0$), top ($z > 0$), botton ($z < 0$).

ARGUMENTS

front – integer
back – integer
right – integer
left – integer
top – integer
botton – integer
dom – mesh structure

MODULES

USE mesh_struct

2.5 build_glob_robin

NAME

build_glob_robin

SYNOPSIS

```
 SUBROUTINE build_glob_robin (front,back,right,left,top,botton,     &
&                             dom)
```

DESCRIPTION

Detect robin facet on face of domain with the convention front ($x > 0$), back ($x < 0$), right ($y > 0$), left ($y < 0$), top ($z > 0$), botton ($z < 0$).

ARGUMENTS

front – integer
back – integer
right – integer
left – integer
top – integer
botton – integer
dom – mesh structure

MODULES

USE mesh_struct

2.6 build_glob_neumann

NAME

build_glob_neumann

SYNOPSIS

```
 SUBROUTINE build_glob_neumann (front,back,right,left,top,botton,   &
&                               dom)
```

DESCRIPTION

Detect clamped facet on face of block with the convention front ($x > 0$), back ($x < 0$), right ($y > 0$), left ($y < 0$), top ($z > 0$), botton ($z < 0$).

ARGUMENTS

front – integer
back – integer
right – integer
left – integer
top – integer
botton – integer
dom – mesh structure

MODULES

USE mesh_struct

2.7 build_glob_mesh

NAME

build_glob_mesh

SYNOPSIS

```
SUBROUTINE build_glob_mesh (ni,nj,nk,dx,dy,dz,dom)
```

DESCRIPTION

Compute geometry and coordinates of regular hexaedric mesh.

ARGUMENTS

ni – integer
nj – integer
nk – integer
dx – real
dy – real
dz – real
dom – mesh structure

MODULES

USE mesh_struct

2.8 imove

NAME

imove

SYNOPSIS

```
SUBROUTINE imove (dim,x,y)
```

DESCRIPTION

Move integer array.

ARGUMENTS

dim – integer
x – integer array
y – integer array

2.9 rmove

NAME

rmove

SYNOPSIS

```
SUBROUTINE rmove (dim,x,y)
```

DESCRIPTION

Move real array.

ARGUMENTS

dim – integer
x – real array
y – real array

2.10 echo_dirichlet

NAME

echo_dirichlet

SYNOPSIS

```
SUBROUTINE echo_dirichlet (file_num,dom,frequency,theta,phi)
```

DESCRIPTION

Write list of clamped nodes with Dirichlet boundary conditions.

ARGUMENTS

file_num – integer
dom – mesh structure
frequency – real
theta – real
phi – real

MODULES

USE mesh_struct

2.11 echo_neumann

NAME

echo_neumann

SYNOPSIS

```
 SUBROUTINE echo_neumann (file_num,dom,frequency,theta,phi,         &
&                         frontR,backR,rightR,leftR,topR,bottonR,   &
&                         frontN,backN,rightN,leftN,topN,bottonN)
```

DESCRIPTION

Write rhs associated to Robin and/or Neumann boundary conditions.

ARGUMENTS

file_num – integer
dom – mesh structure
frequency – real
theta – real
phi – real
frontR – integer
backR – integer
rightR – integer
leftR – integer
topR – integer
bottonR – integer
frontN – integer
backN – integer
rightN – integer
leftN – integer
topN – integer
bottonN – integer

MODULES

USE mesh_struct

2.12 echo_coor

NAME

echo_coor

SYNOPSIS

```
SUBROUTINE echo_coor (file_num,space_dim,numb_nodes,coordinates)
```

DESCRIPTION

Write coordinates of nodes.

ARGUMENTS

file_num – integer
space_dim – integer
numb_nodes – integer
coordinates – real array

2.13 echo_geom

NAME

echo_geom

SYNOPSIS

```
 SUBROUTINE echo_geom (file_num,nodes_per_element,numb_elements,    &
&                      geometry,region,type_elem)
```

DESCRIPTION

Write topology.

ARGUMENTS

file_num – integer
nodes_per_element – integer
numb_elements – integer
geometry – integer array
region – integer
type_elem – integer

2.14 echo_mesh

NAME

echo_mesh

SYNOPSIS

```
 SUBROUTINE echo_mesh (file_num,dom)
```

DESCRIPTION

Write mesh.

ARGUMENTS

file_num – integer
dom – mesh structure

MODULES

USE mesh_struct

2.15 echo_splitting

NAME

echo_splitting

SYNOPSIS

```
 SUBROUTINE echo_splitting (file_num,numb_elem,elem2subdom,         &
&                           numb_facet,facet2subdom)
```

DESCRIPTION

Write element to subdomain correspondance including facet element.

ARGUMENTS

file_num – integer
numb_elem – integer
elem2subdom – integer array
numb_facet – integer
facet2subdom – integer array

2.16 inivec

NAME

inivec

SYNOPSIS

```
 SUBROUTINE inivec (lx,x)
```

DESCRIPTION

Pseudo random number generator.

ARGUMENTS

lx – integer
x – complex array

Acknowledgements

The authors acknowledge partial financial support by the European Community under the Enhancing Access to Research Infrastructure action of the Improving Human Potential programme, contract number HPRI-1999-CT-0026.